

1626

Air

Pelican understands that finding the right protection, with the perfect fit for your gear, is a priority. Pelican™ Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Pelican's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Pelican's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Pelican has you covered.

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- · Business card holder
- Quiet rolling stainless-steel bearing wheels
- Press and Pull™ Latches
- Super-light proprietary HPX^{2™} Polymer up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck[™] foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- · Made in the USA
- Limited Lifetime Warranty (Where applicable by law)



CONFIGURATIONS



1626 Standard



1626WF With Foam



1626NF No Foam



1626WDWith Padded Dividers

DIMENSIONS

Interior (L×W×D) 28.14 x 14.10" x 11.72 (71.5 x 35.8 x 29.8 cm) Exterior (L×W×D) 31.12 x 17.05" x 13.33 (79 x 43.3 x 33.9 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 9.72" (24.7 cm)

 Total Depth
 11.72" (29.8 cm)

 Int Volume
 2.69 ft³ (0.076 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Proprietary Polypropylene Blend

Latch ABS

O-Ring EPDM Purge Body ABS

Purge Vent Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLORS



WEIGHT

 Weight With Foam
 18.10 lbs (8.2 kg)

 Weight Empty
 14.65 lbs (6.6 kg)

 Buoyancy
 185.32 lbs (84.1 kg)

TEMPERATURE

Minimum Temperature $-60\,^{\circ}\text{F}\ (-51.1\,^{\circ}\text{C})$ **Maximum Temperature** $160\,^{\circ}\text{F}\ (71.1\,^{\circ}\text{C})$

ACCESSORIES



1626AirFS 8 pc. Replacement Foam Set



1626AirDSPadded Divider Set



1500CICorrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 08-28-24