



iM3220

Storm

Long Case

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Six Press & Pull Latches
- Guaranteed For Life
- Two Padlockable Hasps
- Two Double-layered, Soft-grip Handles
- Vortex™ Valve
- Powerful Hinges
- O-ring seal
- Lightweight Strong HPX® Resin



CONFIGURATIONS



iM3220
Standard



iM3220-X0000
No Foam



iM3220-X0001
With Foam

DIMENSIONS

Interior (L×W×D)	44.00 x 14.00" x 8.50 (111.8 x 35.6 x 21.6 cm)
Exterior (L×W×D)	47.20 x 16.50" x 9.20 (119.9 x 41.9 x 23.4 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	6.50" (16.5 cm)
Total Depth	8.5" (21.6 cm)
Int Volume	3.03 ft³ (0.086 m³)
Padlock Hole Diameter	0.38" (1 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend

Purge Vent

Gortex membrane

COLORS Black OD Green

WEIGHT

Weight With Foam	24.80 lbs (11.2 kg)
Weight Empty	20.40 lbs (9.3 kg)
Buoyancy	188.32 lbs (85.4 kg)
Master Pack Weight	32.00 lbs (14.5 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS**IP67**

OTHER

Master Pack	1
Military	yes

ACCESSORIES

iM3220-FOAM
5 pc. Replacement Foam Set



iM-STRAP-S-VER2
Padded Shoulder Strap



iM-LIDSTAY
Lid Stay



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1500CI
Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 08-29-24